

### REMARKS

Claims 1, 3-7, 9-18, 21-28, and 30-38 are pending in this application, with claims 1, 7, 13, and 28 being in independent form. Dependent claim 17 has been canceled. Claims 1, 7, 13, 16, 23, 27 and 28 have been amended. The amendments to claims 16, 23 and 27 correct minor claim wording. No new matter has been added. Reconsideration of the above-identified application, as herein amended and in view of the following remarks, is respectfully requested.

Claims 1, 3-7, 9-18, 2-28 and 30-38 stand rejected under 35 U.S.C. §103(a) as being unpatentable over U.S. Pub. No. 2003/0122679 ("*Matsushima*") in view of U.S. Patent No. 5,801,634 ("*Young*"), and further in view of U.S. Patent No. 6,697,695 ("*Kurihara*"). For the following reasons, reconsideration and withdrawal of this rejection is requested.

Independent claim 1 has been amended to recite "a plurality of spatially distributed production units, each production unit comprising means for generating and indicating fault signals, each production unit being associated with a transmitting unit configured for to wirelessly transmit the fault signals, two or more of said production units being arranged to form at least one group a plurality of groups of production units" and "a plurality of stationary data receiving units configured to transmit the fault signals to the fault alarm box, each of the plurality of stationary data receiving units comprising a lamp, each of the plurality of stationary data receiving units being configured to wirelessly receive the fault signals from one of the plurality of groups of production units and to indicate the fault signals, the lamp being configured to visually display the fault signals".

Independent claim 13 recites corresponding limitations, and independent claims 7 and 28 each recite a corresponding method step with similar limitations. As described in more detail below, the combination of the cited art fails to teach or suggest the above limitations because the

fabrication apparatuses of *Matsushima* are not each arranged into a plurality of groups of production units, where a respective one of the plurality of groups of productions units is associated with a respective one of a plurality of stationary data receiving units.

The Examiner (at pg. 3 of the Office Action) asserts that:

*Matsushima* teaches ... at least one stationary data receiving unit configured for transmitting the fault signals to the fault alarm box (fig. 3 element 32). (Emphasis Added)

Applicants disagree.

*Matsushima* relates to a plurality of fabrication apparatuses 12 arranged in series for performing a sequential processing of work units applied to a system. That is, *Matsushimai* discloses a fabrication apparatus that includes special equipment interconnected by a wired "backbone".

The Examiner associates the lamp control signal monitor 32 with the claimed stationary data receiving unit, as shown in Fig. 3 of *Matsushima*. Paragraph [0029] of *Matsushima* explains that the lamp control signal monitor 32 is included in the fabrication apparatus 12, and that "[t]he lamp control signal monitor 32 is directly concerned with the present invention". *Matsushima* (paragraph [0032], lines 1-4) further explains that "[t]he lamp control signals, outputted from the controller 28, are also applied to the lamp control signal monitor 32, which comprises a parallel interface 42, a serial interface 44, a microprocessor unit (MPU) 46, and a memory 48". *Matsushima* (paragraph [0032], lines 4-13) additionally explains that "[t]he lamp control signal monitor 32 is operatively coupled to the display 22, a display control switch 50, and the personal computer 52. The computer 52 serves to load suitable software to the CPU 46, and applies date-and-time information to the MPU 46, and collecting the data stored in the memory 48. Further, the computer 52 is coupled to a plurality of lamp control signal monitors of the other fabrication apparatuses (not shown in FIG. 3 but best shown in FIG. 4)".

In contrast, the claimed invention includes a plurality of stationary data receiving units configured to transmit the fault signals to the fault alarm box, each of the plurality of stationary data receiving units comprising a lamp, each of the plurality of stationary data receiving units being configured to wirelessly receive the fault signals from a plurality of groups of production units and to indicate the fault signals, the lamp being configured to visually display the fault signals, as recited in now amended independent claim 1. Independent claim 1 additionally recites “a plurality of spatially distributed production units, each production unit comprising means for generating and indicating fault signals, each production unit being associated with a transmitting unit configured to wirelessly transmit the fault signals, two or more of said production units are being arranged to form a plurality of groups of production units”. That is, in accordance with the claimed invention, production units are arranged into a plurality of groups of production units. In addition, a plurality of stationary data receiving units are provided, where each stationary data receiving unit is dedicated to exactly one group of production units.

Consequently, it is possible for one stationary data receiving unit to show faults of several production units within its respective group, where the production units are members of the same group. Faults of other production units, which are members of another or second group, however, are signaled to another or a second stationary data receiving unit. There is arrangement of the fabrication apparatuses of *Matsushima* into a plurality of fabrication apparatuses, where each group of fabrication apparatuses is provided with a lamp control signal monitor. In all cases, *Matsushima* depicts a single group of fabrication apparatuses. However, there is no duplication of this single group of apparatuses to provide a plurality of the groups of apparatuses. Accordingly, there is no teaching or suggestion in *Matsushima* of “two or more of said production units being arranged to form a plurality of groups of production units” and “a

respective one of the plurality of groups of production units being associated with a respective one of the plurality of stationary data receiving units”, as recited in independent claim 1. Independent claim 13 recites “a plurality of groups comprising a number of said production units, each respective one of the plurality of groups being associated with a respective one of the plurality of stationary data receiving units configured to wirelessly receive fault signals transmitted by the transmitting unit associated with any production unit in said respective group”. Independent claims 7 and 28 recite a corresponding method step. There is no teaching or suggestion in *Matsushima* of these limitations.

*Young* has been cited to provide a teaching “that the monitoring controller can be separate and include a light tower”. *Kurihara* has been cited to provide a teaching that “a group of multiple units can be monitored by a single monitor”. *Young* relates to “a monitoring system that permits the early detection of an error condition that most probably will result in a batch of wafers that are out of specification and must be scrapped” (see col. 2, lines 21-24). *Kurihara* relates to “a laser device management system wherein data indicating the state of the laser device is acquired by gathering data at predetermined events, thereby allowing it to predict the lifetime of consumable components and predict problems with the laser device before they occur, from a remote location” (see col. 2, lines 35-40).

However, *Young* and *Kurihara* are silent with respect to two or more production units arranged to form a plurality of groups of production units, where a respective one of the plurality of groups of productions units is associated with a respective one of the plurality of stationary data receiving units. Accordingly, the combination of *Matsushima*, *Young* and *Kurihara* fails to achieve the expressly recited subject matter of independent claims 1, 7, 13 and 28, because *Young* and *Kurihara* fails to provide what *Matsushima* lacks.

In view of the foregoing, independent claim 1, 7, 13 and 28 are patentable over *Matsushima, Young and Kurihara*, individually or in combination. Reconsideration and withdrawal of the rejection under §103(a) are therefore in order, and a notice to that effect is respectfully requested.

In view of the patentability of independent claims 1, 7, 13 and 28, dependent claims 3-6, 9-12, 14-16, 18, 21-27 and 30-38 are also patentable over the prior art for the reasons set forth above, as well as for the additional recitations contained therein.

Based on the foregoing remarks, this application is in condition for allowance. Early passage of this case to issue is respectfully requested.

Should the Examiner have any comments, questions, suggestions, or objections, the Examiner is respectfully requested to telephone the undersigned in order to facilitate reaching a resolution of any outstanding issues.

Respectfully submitted,  
COHEN PONTANI LIEBERMAN & PAVANE LLP

By /Alfred W. Froebrich/  
Alfred W. Froebrich  
Reg. No. 38,887  
551 Fifth Avenue, Suite 1210  
New York, New York 10176  
(212) 687-2770

Dated: April 19, 2010